

Avida

Manufacturing Conveying



Perfect for clay and brick

Reliable, rapid order fulfillment with low cost of ownership

Avida Specifications	
Method of Conveying	Aero-mechanical (AMC)
Conveyor Size	3" (76.2mm) 4" (101.6mm)
Internal Material Contact Parts	Carbon Steel (Painted) [Optional] Stainless Steel
External Non-Contact Parts	Carbon Steel (Painted)
External Welding	Stitch
Internal Welding	Continuous, Left "as Laid"
Internal Finishing	Powder Coated Carbon Steel, Glass Bead Blasting Stainless Steel
External Finishing	Carbon Steel Painted
Tubes	Stainless Steel Tube
Motor	IP55, Aluminium / Painted Cast Iron Housing
Drive – Ex Upgrade	[Optional] Geared Motor Upgraded to Ex d/Ex e
Safety as standard	EN ISO 12100 - 1:2010 Compliant

Avida Specifications cont.

Accessibility	
Tooled Access Throughout	Standard
Maintenance	
Manual Tension Adjustment	Yes

Equipment Available in Avida Range



Mobile Systems



Get in touch with us
[floveyor.com](https://www.floveyor.com)

Our powder handling specialists are available to advise you on how a Floveyor from the Avida range can streamline your bulk material handling operations.